

BlackBox Component Builder - Bug #77

DevCPT.InSign should use outBit instead of inBit for outPar

10/12/2015 02:14 PM - J. Templ

Status:	Closed	Start date:	10/12/2015
Priority:	Normal	Due date:	
Assignee:	J. Templ	% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:	1.7		
Forum topic:			
Description			
<p>DevCPT.InSign uses inBit for both inPar and outPar instead of using outBit for outPar. A proposal by Oleg N. Cher for the required change exists in CPC 1.7 rc5. Reported by Oleg N. Cher, 2014-07-16.</p> <p>Refers to CPC 1.7 rc5 change list number 64.</p>			

Associated revisions

Revision 4b3f790a - 10/12/2015 02:41 PM - J. Templ

InSign uses outBit instead of inBit for outPar. Refs: #77.
As proposed by Oleg N. Cher in CPC 1.7 rc5.

Signed-off-by: Josef Templ <josef.templ@gmail.com>

Revision 0f57b355 - 10/22/2015 09:27 PM - I. Denisov

Merge pull request #66 from BlackBoxCenter/issue-#77

InSign uses outBit instead of inBit for outPar. Refs: #77.

History

#1 - 10/12/2015 02:18 PM - J. Templ

- Description updated

#2 - 10/12/2015 02:39 PM - J. Templ

- Subject changed from DevCPT.InSign should use outBit instead of inBit for outPar to DevCPT.InSign should use outBit instead of inBit for outPar

#3 - 12/03/2015 12:47 PM - J. Templ

- Status changed from New to Closed